

FIGURE 1




FIGURE 2





FIGURE 3






FIGURE 5

500

IP HEADER <u>502</u>			
UDP HEADER <u>504</u>			
TYPE <u>506</u>	RESERVED <u>508</u>	LENGTH <u>510</u>	
HEARTBEAT INTERVAL <u>512</u>		RESERVED <u>514</u>	
FOREIGN AGENT ADDRESS <u>516</u>			
SUBTYPE CALL LOAD <u>518</u>	LENGTH <u>520</u>	FOREIGN AGENT CALL LOAD <u>522</u>	
SUBTYPE CPU USAGE <u>524</u>	LENGTH <u>526</u>	FOREIGN AGENT CPU USAGE <u>528</u>	
SUBTYPE MEMORY USAGE <u>530</u>	LENGTH <u>532</u>	FOREIGN AGENT MEMORY USAGE <u>534</u>	
FH AUTH TYPE <u>536</u>	LENGTH <u>538</u>	SPI <u>540</u>	
SPI <u>542</u>		AUTHENTICATOR... <u>544</u>	
AUTHENTICATOR...			

FIGURE 6

600

IP HEADER <u>602</u>			
UDP HEADER <u>604</u>			
TYPE <u>606</u>	RESERVED <u>608</u>	LENGTH <u>610</u>	
PDSN ADDRESS <u>612</u>			
KEY TAG VALUE <u>614</u>		RESERVED <u>616</u>	
SUBTYPE PDSN-RNN KEY <u>618</u>	LENGTH <u>620</u>	SPI <u>622</u>	
SPI		SECRET <u>624</u>	
...SECRET (CONTINUED)			
...SECRET (CONTINUED)			
...SECRET (CONTINUED)			
SECRET <u>624</u>	SUBTYPE PDSN-AAA KEY <u>626</u>		LENGTH <u>628</u>
FAAA IP ADDRESS <u>630</u>			
...SECRET (CONTINUED)			
...SECRET (CONTINUED)			
...SECRET (CONTINUED)			
...SECRET			
FH AUTH TYPE <u>634</u>	LENGTH <u>636</u>	SPI <u>638</u>	
SPI		AUTHENTICATOR ... <u>640</u>	

FIGURE 7







FIGURE 8A






**FIGURE 8B**







**FIGURE 10A**




**FIGURE 10B**



**FIGURE 10C**



# FIGURE 11



# FIGURE 12




FIGURE 13

